


INVITATION OF EXPRESSION OF INTEREST (EOI) FOR NDRF EQUIPMENT

1. NDRF is the lead federal force responsible for responding to all types of natural and man-made disasters. NDRF acknowledges the importance of having reliable equipment to enhance the efficiency and effectiveness of rescue operations.
2. NDRF now intends to procure **Light Weight Emergency Tent** for the NDRF Teams. Accordingly, NDRF has prepared a draft technical specification for the **Light Weight Emergency Tent** required to enhance the efficiency and effectiveness of rescue operations. The draft specifications are appended as **Appendix- A**.
3. In this context, NDRF invites Expressions of Interest (Eoi) from eligible manufacturers, suppliers and vendors to submit their comments and suggestions. In case these specifications do not match with the available equipment in the market, the same may be highlighted and the specification of the equipment available in the market may kindly be provided with the same functionality. The purpose of the Eoi document is to provide necessary information to NDRF so that genuine and generalized specifications can be framed and finalized for further procurement, and no gap exists in the specifications of the items available in the market out the specificness floated in the bid by NDRF.
4. This EOI is not an offer by NDRF or a tender document but it is an invitation to receive responses from eligible manufacturers, suppliers, and vendors in the industry the draft specification framed by NDRF.
5. Eligibility Criteria: The minimum eligibility criteria for an entity to participate in the Eoi is as follows: -
 - i. The entity must be a manufacturer or vendor/supplier/dealer registered in India under relevant applicable Acts and Laws.
 - ii. The entity must have some experience in the supply of such equipment.
 - iii. NDRF may call manufacturers, suppliers and vendors to conduct the demonstration/field trial of such equipment if needed before finalizing the specification
7. Documents to be submitted: The following documents are required to be submitted as part of the response to this Eoi.
 - i. Documents supporting Eligibility Criteria as mentioned above.
 - ii. List of equipment catalogue with detailed technical specifications along with estimated cost if possible.
6. Eligible manufacturers, suppliers and vendors who have the competence and experience to carry out such work are requested to submit the suggestion/comments (Eoi) along with supporting documents within 21 days.

-Important timelines-

Event	Timeline
Last date of submission of responses	Within 21 Days


05-02-26

(Manmeet Singh Azad)
DC (R&D)
HQ NDRF

No. 1-17018/R&D/SRC/HQ NDRF/2025/73

Dated 05/02/2026

Light Weight Emergency Tent (LWET)

Specifications and requirements

S/No.	Requirement	Remark, if any
1	General Condition	
1.1	The maximum weight of the tent is 42 kg (\pm 5%) included inner and outer shells, 6 rods, 18 pegs (12 larges and 6 mediums), 1 hammer (0.8 kg) and packaging.	BOO to physical check and verify.
1.2	The outer shell, the inner tent and all the accessories bags shall be packed in one single bag made out of the outer shell material with two carrying handles (the bag of rods must be packed in the centre of the bundle). The bag will be in a strong transparent polyethylene and covered with Polyethylene bag. It will have two plastic straps to hold it together.	BOO to physical check and verify.
1.3	Assembling instructions of the tent made with laminated A4 paper must be included on top of each packaging.	BOO to physical check and verify.
1.4	Marking of NDRF INDIA logo (50 cm x 15 cm) to be printed in blue indelible ink on one side of the single bag	BOO to physical check and verify.
1.5	Marking of NDRF INDIA logo to be printed in blue indelible in, colour Pantone N°PMS 300C included Purchase Number, Project symbol, Consignee and Content (60 cm x 40 cm) on one side of the polyethylene bag	BOO to physical check and verify.
1.6	The craftsmanship on this product needs to be of highest quality.	BOO to physical check and verify.
2	Outer Shell	
2.1	Woven polyester of rip stop weaves of single piece i.e. with no cut pieces being joined.	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
2.2	Basic weight 170-190 grams/m ² .	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
2.3	The outer shell is of white colour (Pantone N° 11-0602 TPX) from out sides.	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
2.4	Free of weaving defects that would have a negative effect on strength, waterproof quality and durability.	BOO to check and verify through OEM certificate
2.5	Able to withstand a minimum of 3000 mm of static water column.	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
2.6	Outer shell must have a UV resistance of a minimum of 2000 hours of exposures.	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
2.7	Outer shell must have fire resistance according to CPAI-84 1955 standards / section 6.	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)

S/No.	Requirement	Remark, if any
2.8	5 sleeves continuous and integrated of 4 cm width with no breaks (for the ease of rod insertion) to house the tension rods for holding the outer shell and from which the inner tent would be suspended.	BOO to physical check and verify.
2.9	All seams to be double-locked stitched, and supported with anti-leak/anti-seepage water taping. The supplier will ensure that the stitch count and thread used for all parts of the tent are appropriate for the material and will produce strong, long lasting (both on the shelf and in use) and that these of highest degree of craftsmanship. Low quality workmanship on any point is categorically unacceptable.	BOO to check and verify through OEM certificate
2.10	Strong and rot-proof ground of 10 reinforcement patches located at the ends of sleeves around the perimeter of the tent (5 on each side) with a metallic triangle. End of rods will be inserted in the hole and fixed to the ground.	BOO to physical check and verify.
2.11	The outer shell should have 10 triangular reinforcements at each pegging point to avoid tearing of the material. The reinforcement triangle must be made of the same material as the outer shell.	BOO to check and verify through OEM certificate
2.12	A polyester strap with an average width of between 35 to 40 mm and strength to carrying 100 Kg loading, rot-proof equipped with a metallic triangle and a metallic buckle at one side of the tension rod to hold both ends of tension rod at a distance of 3.00 meters from one another.	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
2.13	The outer shell at each end of the tension rods should be connected with the strap in order to avoid twisting.	BOO to physical check and verify.
2.14	Four windows (two on each long side) with a size of 40 cm x 30 cm each, located at 1m from the ground, covered with mosquito (ASTM Mesh 18) which is used for strength and ventilation. The covered flap must be equipped with Velcro all around the perimeter. The windows should be able to be rolled up and fixed up with toggles. Windows must be located on alternate panels on the two sides and not directly facing each other.	BOO to physical check and verify.
2.15	Four integrated ventilation flap openings with mosquito net (ASTM Mesh 18) of minimum aperture covered with a triangle ring hood (base 30cm, height 40 cm). The size of each ventilation opening shall be 20 cm x 15 cm. A Velcro strip must be sewed on the edge of the flap and on the outer shell to be able to keep it closed. In addition for the ventilation mechanism, one reinforced opening strip with outer shell material and PVC strip (width of 2 to 3 cm, length 12 cm) must be sewed in the centre of the edge on the outer shell. The other edge will have a Velcro strip that will allow the hood to stay open.	BOO to physical check and verify.
2.16	A total of 14 mechanisms of guy ropes are well stitched to the outer shell. Three are placed on each side and four at either end of the outer shell. Each guy ropes to the outer shell should be quadruple fold in triangular shape with the same material as outer shell, with a base of 23 cm and sides of 21 and 11 cm connected to both sides of the sleeve holding the tension rods reinforced in the end with a 4 cm polyester webbing with the strength to carry 100 kg equipped with anti-rust metallic	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)

S/No.	Requirement	Remark, if any
	triangle and knot the side rope. In addition each mechanism will have one reinforced eyelet with an internal diameter of minimum 10 millimetres. The location of the connecting mechanism is at 110 cm from the ground level for 10 side ropes (6 time on side + 4 time on edge) and 170 cm from the ground level for 4 side ropes in the end of the tents. Ventilation is placed at 140 cm from the ground level. Windows is placed at 100 cm from the ground level to the lintel position of the window.	
2.17	The outer shell should have a connecting toggle under each tension rod at 26.36 cm (axis to axis) so that the inner shell can be hung from it. The 21 connecting toggles on the outer shell are made of quadruple straps made from outer tent material and equipped with an anti-rust metallic ring in the end. The inner shell connection is made with double polyester webbing (minimum width of 2 cm) with a toggle in the end. One single connection should be strong enough to carry or withstand a loading of 10kg. Webbing and tent material, as shown in the pictures should be the only connector fabrics used. Care should be exercised that the stitches are strong enough to withstand the required loading at a regular distance of 15 cm.	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
2.18	<p>One chimney outlet of 12 cm in diameter made out of fire resistant Fibre Glass fabric to with stand heat up to 500 degree centigrade (BS 476/7:1971 Class1). The hole should be able to be closed tightly to avoid rain and moisture infiltration when heating of the tent is not required.</p> <p>The outlet should be wider towards the bottom to reach a diameter of 30 cm where it will be stitched to the tent. It would be located in the end section 60 cm from the end of tent and located on the side of the tent. The bottom of the hole would be about 140 cm from the ground covered with the same material as the outer shell and covered (60cm X 60cm) with Velcro, similar to the way the windows are covered. This is to prevent any water infiltration when stove is not used. The seam on the upper part should be treated with water sealant, as all other seams being. The outlet will also have a removable cover from the inner tent.</p>	BOO to physical check and verify.
2.19	Markings to be printed in blue indelible ink (Pantone N° PMS 300C) on both sides of the tent and on top of the tent (to be positioned horizontally) for maximum visibility. The width of marking must be 120 cm and the height proportionate to the width without any distortion of the logo and letterings (approximately 35 cm).	BOO to physical check and verify.
3.	Inner shell	
3.1	The inner tent is the same shape as the outer shell but 30 cm narrower leaving a minimum of 15 cm gap (all around) between the outer shell and inner tent. The useable floor area of maximum 14.85 m ² [5.50m x (3.00(0.15+0.15) m). The height would be of maximum 1.95m (2.10m-0.15 m)	BOO to physical check and verify.
3.2	Made of breathable (Less material from a blend of polyester and cotton 65/35 or 55/45.	BOO to check and verify through the lab report

S/No.	Requirement	Remark, if any																		
		(Govt/ Govt accredited NABL/International Lab)																		
3.3	Basic weight of 140-160 gram/m ² , Rip stops weave and fire retardant.	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)																		
3.4	The inner tent shall be blue in colour with Pantone reference N° 17-4023 TPX	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)																		
3.5	All seams shall be double stitched.	BOO to physical check and verify.																		
3.6	Two strips made of double polyester webbing (width of 4 cm) with eyelet in the end must be well stitched with reinforcement in order to properly tighten the ground floor sheet with two pegs in front of each door	BOO to physical check and verify.																		
3.7	One integrated door on either end of the inner shell (total two doors) with mosquito net type ASTM Mesh 7 and zipper of No. 10 (9mm) moulded plastic with double pull slider opening upwards with a back up of button. The doors shall have a height of 165 cm and a width of 100 cm having a 20 cm threshold to prevent insects and water to enter the tent made of same material as the ground sheet. The mosquito net should be of with fine mesh type (ASTM Mesh 7) and equipped with zippers No. 10 moulded plastic with double pull slider on both sides and Velcro on the bottom to prevent mosquitoes to enter the tent. A dart or fold (i.e. a piece of excess material) must be included in both the door and mosquito net to reduce the stress on the zippers. The closing system to roll up the doors and the mosquito net should be fixed on top and made with 4 toggles and 4 straps and rings on each opening side.	BOO to physical check and verify.																		
3.8	<p>Outer and inner tent mosquito net (doors, windows and ventilations openings) must be long lasting insecticide treated in accordance with the WHO standards.</p> <p>WHO recommended insecticides for treatment of mosquito nets for malaria vector control</p> <table border="1"> <thead> <tr> <th>INSECTICIDE</th> <th>FORMULATION</th> <th>DOSAGE (mg/m²)</th> </tr> </thead> <tbody> <tr> <td>Alpha-cypermethrin</td> <td>SC 10%</td> <td>20–40</td> </tr> <tr> <td>Cyfluthrin</td> <td>EW 5%</td> <td>50</td> </tr> <tr> <td>Deltamethrin</td> <td>SC 1% and WT 25%³</td> <td>15–25</td> </tr> <tr> <td>Etofenprox</td> <td>EW 10%</td> <td>200</td> </tr> <tr> <td>Permethrin</td> <td>EC 10%</td> <td>200–500</td> </tr> </tbody> </table> <p>i. SC suspension concentrate; EW-emulsion, oil in water; WT-water dispersible tablet; EC: emulsifiable concentrate.</p>	INSECTICIDE	FORMULATION	DOSAGE (mg/m ²)	Alpha-cypermethrin	SC 10%	20–40	Cyfluthrin	EW 5%	50	Deltamethrin	SC 1% and WT 25% ³	15–25	Etofenprox	EW 10%	200	Permethrin	EC 10%	200–500	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
INSECTICIDE	FORMULATION	DOSAGE (mg/m ²)																		
Alpha-cypermethrin	SC 10%	20–40																		
Cyfluthrin	EW 5%	50																		
Deltamethrin	SC 1% and WT 25% ³	15–25																		
Etofenprox	EW 10%	200																		
Permethrin	EC 10%	200–500																		

S/No.	Requirement	Remark, if any
	ii. Milligrams of active ingredient per square meter of netting	
3.9	The front and back of the inner tent (including the doors) should be double folded; outer fold is made from the same material of outer shell and inner fold is made from same material of inner tent. This double fold shall continue to cover the both ends of inner tent towards the middle for 80 cm deep as well. These provisions increase the durability of the tent, provide cooler temperature and increased resistance to rain accepting the slight increase in the weight.	
3.10	The ground sheeting shall be of dark blue in colour Pantone reference N° 17-4023 TPX. It is made of woven high density polyethylene fibers; warp x weft: 12/14 x 12/14 per square inch, laminated on both sides with low density polyethylene; Material weight: minimum 200 gr/m ² +/- 5%; Tensile strength: minimum 600 N both directions. Tear resistance: minimum 100 N both directions. Water proof: to withstand 2000 mm water column. Stitching: All seams should be treated with anti-leak/anti-seepage water sealant/tape. The stitching of the ground sheet to the inner tent should be about 20cm above the ground level to ensure better resistance to water infiltration. 14 polyester webbing must be well stitched with reinforcement (1 in each corner, 3 on each side and 2 on each edge) in the line with the tension rods and pegs.	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
3.11	Inner shell shall be supported by the outer shell (hung from the outer shell). All rings shall be of rust resistant material. The inner shell shall have a connecting mechanism under each tension rod 23 cm apart from each other. (Total of 21 mechanism for each rod). Care should be exercised that the stitches are strong enough to withstand the loading. Distance between the outer shell and the inner tent must be 15 cm minimum.	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
3.12	The connection at each ends of the tension rods must have an adjustable buckle as shown in the.	BOO to physical check and verify.
3.13	Four integrated windows for ventilation (in line with the outer shell window) with mosquito net type ASTM Mesh 7 and fully covered with the same material equipped with Velcro, to be rolled up (hold-up with toggle and strap with ring). The windows shall have a height of 30 cm and a width of 40 cm.	BOO to physical check and verify.

S/No.	Requirement	Remark, if any
3.14	Four integrated ventilation openings at the top (two on each side) to be aligned to the ventilation opening hood of the outer shell (with no cover).	BOO to physical check and verify.
3.15	The inner shell should be partitioned in the middle dividing the tent into two twin sections of 2.75m X 2.76m = 7.59 m ² .	BOO to physical check and verify.
3.16	The partitioning consists of two sections, which will be stitched to the inner tent with 40 cm overlapping in the middle equipped with 4 tie straps and toggles on both side. The partition can be rolled back to the sides with tie strap and toggle to hold it on both sides of the tent. The material is the same as inner tent, and must not be of transparent material.	BOO to physical check and verify.
3.17	The inner tent will have a canopy of 150 cm stitched across the top and coming out from the tent a distance of 100 cm on the both ends of the inner tent. The canopy, which is of the same material as the outer tent, is stitched to the upper ends of the inner tent and equipped with two eyelets (1 in each corner) to be able to tie it with a guy rope to the existing pegs. The tightening system with toggle and tie strap must also be fixed on top of the canopy to be able to be rolled up when not in use.	BOO to physical check and verify.
3.18	A pocket of transparent plastic for inserting an A4 paper in landscape to be fixed to both ends of the inner tent on the left side of the door. This should be close to the edge of the tent and 1.00 m from the ground taped with water sealing tape	BOO to physical check and verify.
4	Support system	
4.1	6 tension rods should be of solid fibre glass reinforced with black PVC wrapper, with odd number of tubular sleeves or internal rod connector pins. The diameter of the rod must be at minimum of 20 mm (17mm of fibre glass and 2 x 1.5mm of PVC wrapper). The rods should be "shock-corded" (having a cord inside the rod). The joints shall be easy to assemble and should be sufficiently reinforced to avoid any possible breakage. One rod is composed of 9 sections of 68 cm (Total length 580 cm). Each section fit together at a minimum of 4 cm in the connector pins.	BOO to physical check and verify.
4.2	The ends of the tension rods are anchored to the ground with aluminium or brass eyelet in the strap connecting the both sides of tension rod in place, the metallic ends of the tension rods must be at minimum 5.0 cm long at each end to ensure better fixation of the frame to the strap and to the ground.	BOO to physical check and verify.
5	Side and Guy Ropes	
5.1	Guy ropes should be made of polyester fibre (multi-braided type), having a diameter of 6 mm and length of 3.00 meters for the side ropes and the canopy and a length of 3.50 meters for the other guy ropes that are attached to the upper part of either end of the tent. The strength of the guy ropes should not be less than 250 Kg. Guy ropes should have a UV resistance of a minimum of 2000 hours of exposures.	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
5.2	Six guy ropes on each end of the tent and three on each long side of the outer shell hence gives a total of 18 guy ropes to be able to erect the tent. In addition 1 spare of 3.00 meters and one spare of 3.50 meters must also be provided that will raise a total number of 20 guy ropes. All ropes are equipped with a simple and light tightening mechanism. This mechanism must be made with a varnished hard wood (e.g. oak) with two holes as describe on the.	BOO to physical check and verify.

S/No.	Requirement	Remark, if any																																													
6	Pegs and Hammer																																														
6.1	Pegs for the outer shell must be of corrugated (deformed) steel having a length 30 cm and diameter 12 mm, with provision of a smooth "U" shaped bend to hook and tie up the guy ropes and tapered in the other end. A total of 10 corrugated steel pegs for outer shell are required with 2 spares (total of 12 pegs). The pegs are tapered at one end to ensure easy anchoring into the ground and covered with simple coating of non rust paint.	BOO to physical check and verify.																																													
6.2	Pegs for tightening the ground sheet at the two entry door must be of corrugated (deformed) steel having a length 20 cm and diameter 8 mm, with provision of a smooth "U" shaped bend to hook and tie up the guy ropes and tapered in the other end. A total of 4 pegs are required with bin addition one spare (Total of 5 pegs). The pegs are tapered at one end to ensure easy anchoring into the ground and covered with simple coating of paint.	BOO to physical check and verify.																																													
6.3	A claw hammer with a minimum weight of 0.8 kg for hammering the pegs with a sufficient strong head to handle connection for pegs insertion must also be provided.	BOO to physical check and verify.																																													
7	Shape Size and Construction																																														
7.1	The tent is semi-circular or tunnel shaped with centre height of 210 cm, width of 300 cm and length of 550 cm.	BOO to physical check and verify.																																													
7.2	It consists of two full layers or double flies i.e.a water proof outer shell and an inner tent with 15 cm continuous distance between them.	BOO to physical check and verify.																																													
7.3	The inner tent, which is with integrated flooring ("bathtub" ground sheeting), is hung from the outer shell and tight with 10 webbing in each end of rods. 4 additional pegs in front each doors will reinforced the stability of the ground sheet	BOO to physical check and verify.																																													
7.4	The outer shell acts as a pure "shell" and not as a "tent"																																														
8	<table border="1"> <thead> <tr> <th>Ref</th> <th>Item description</th> <th>Test Method</th> <th>Requirements</th> <th>Tolerances</th> </tr> </thead> <tbody> <tr> <td colspan="5">2. Outer Shell</td> </tr> <tr> <td>2.1</td> <td>Woven polyester Rip Stop</td> <td>EN 1049</td> <td>Pass</td> <td>Nil</td> </tr> <tr> <td>2.2</td> <td>Fabric weight</td> <td>ISO 3801</td> <td>170–190 g/m²</td> <td>Nil</td> </tr> <tr> <td>2.3</td> <td>Colour shade</td> <td>ISO 3801</td> <td>< ΔE 1.0</td> <td>0.2</td> </tr> <tr> <td>2.5</td> <td>Waterproof (Hydrostatic head)</td> <td>ISO 811</td> <td>3000 mm</td> <td>Nil</td> </tr> <tr> <td>2.6</td> <td>Tensile Strength after UV exposure (ISO 4892-3 Method 2)</td> <td>ISO 12934</td> <td>< 50%</td> <td>Nil</td> </tr> <tr> <td>2.7</td> <td>Fire Resistance</td> <td>CPAI-84/6</td> <td>Pass</td> <td>Nil</td> </tr> <tr> <td>2.12</td> <td>Polyester strap</td> <td>ISO 13934</td> <td>10.0 Kg</td> <td>±5%</td> </tr> </tbody> </table>	Ref	Item description	Test Method	Requirements	Tolerances	2. Outer Shell					2.1	Woven polyester Rip Stop	EN 1049	Pass	Nil	2.2	Fabric weight	ISO 3801	170–190 g/m ²	Nil	2.3	Colour shade	ISO 3801	< ΔE 1.0	0.2	2.5	Waterproof (Hydrostatic head)	ISO 811	3000 mm	Nil	2.6	Tensile Strength after UV exposure (ISO 4892-3 Method 2)	ISO 12934	< 50%	Nil	2.7	Fire Resistance	CPAI-84/6	Pass	Nil	2.12	Polyester strap	ISO 13934	10.0 Kg	±5%	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
Ref	Item description	Test Method	Requirements	Tolerances																																											
2. Outer Shell																																															
2.1	Woven polyester Rip Stop	EN 1049	Pass	Nil																																											
2.2	Fabric weight	ISO 3801	170–190 g/m ²	Nil																																											
2.3	Colour shade	ISO 3801	< ΔE 1.0	0.2																																											
2.5	Waterproof (Hydrostatic head)	ISO 811	3000 mm	Nil																																											
2.6	Tensile Strength after UV exposure (ISO 4892-3 Method 2)	ISO 12934	< 50%	Nil																																											
2.7	Fire Resistance	CPAI-84/6	Pass	Nil																																											
2.12	Polyester strap	ISO 13934	10.0 Kg	±5%																																											

S/No.	Requirement					Remark, if any
		Tensile Strength				
2.16	Ropes Tensile Strength	IHTM	100.0 Kg	±5%		
1.17	Connecting mechanism tensile strength	IHTM	10.0 Kg	±5%		
2. Inner Shell (Upper)						
3.2	Fibre content	ISO 1833	PL 55 / CO 45	±3%		
3.3	Fabric Weight	ISO 3801	140–160 g/m ²	±5%		
	Fire Resistance	CPAI-84/6	Pass	Nil		
3.4	Colour shade	ISO 105 J03	< ΔE 1.0	0.2		
3. Inner Shell (Ground Sheet)						
3.10	Fibre content	GS-MS / FTIR	Polyethylene	Nil		
	Waterproof (Hydrostatic head)	ISO 811	2000 mm	Nil		
3.11	Colour Shade	ISO 105 J03	< ΔE 1.0	±0.2		
	Number of threads per Unit Length	ISO 7211/2-C	12–14 / inch	Nil		
	Fire Resistant	CPAI-84/5	Pass	Nil		
	Fabric weight	ISO 3801	200 g/m ²	±5%		
	Tensile strength	ISO 5081	600 N	±5%		
	Tear strength	ISO 4674-A2	100 N	±5%		
5.	Side and Guy Ropes					
	Ref	Item description	Test Method	Requirements	Tolerances	BOO to check and verify through lab report (Govt/ Govt accredited NABL/International Lab)
	5.1	Ropes Tensile Strength	ISO 13934	250.00 Kg	±5%	

बिड दस्तावेज़ / Bid Document

बिड विवरण/Bid Details	
बिड बंद होने की तारीख/समय /Bid End Date/Time	26-02-2026 16:00:00
बिड खुलने की तारीख/समय /Bid Opening Date/Time	26-02-2026 16:30:00
बिड पेशकश वैधता (बंद होने की तारीख से)/Bid Offer Validity (From End Date)	180 (Days)
मंत्रालय/राज्य का नाम/Ministry/State Name	Ministry Of Home Affairs
विभाग का नाम/Department Name	Central Armed Police Forces
संगठन का नाम/Organisation Name	National Disaster Response Force (ndrf)
कार्यालय का नाम/Office Name	Hq Ndrf New Delhi
कुल मात्रा/Total Quantity	1
वस्तु श्रेणी /Item Category	Eol Light Weight Emergency Tent (LWET)
GeMARPTS में खोजी गई स्ट्रिंग्स / Searched Strings used in GeMARPTS	Light Weight Emergency Tent (LWET)
GeMARPTS में खोजा गया परिणाम / Searched Result generated in GeMARPTS	Emergency Light Unit (V2), Emergency lighting and accessories (Portable Emergency Lighting System Tower type with Battery Bank), Flameproof LED Emergency Light, Light Weight Web Equipment, Light Weight Folding Rectangular Table, Light Weight Sleeping Bag (Improved) - CAPF (V2), Bag Sleeping Light Weight (Defence), Multipurpose Light Weight Kulhari (Axe), Compact Light Weight Stainless Steel Multi Utility Tool (MHA), Vemavaram Light weight Sarees from West Godavari - ODOP
अधिसूचना के लिए चयनित प्रासंगिक श्रेणियाँ / Relevant Categories selected for notification	<ul style="list-style-type: none"> Inflatable Tent Flexi Tent tent arctic camping and outdoor equipment
वर्षों के अनुभव एवं टर्नओवर से एमएसई को छूट प्राप्त है / MSE Relaxation for Years Of Experience and Turnover	Yes Complete
स्टार्टअप के लिए अनुभव के वर्षों और टर्नओवर से छूट प्रदान की गई है / Startup Relaxation for Years Of Experience and Turnover	Yes Complete

बिड विवरण/Bid Details	
विक्रेता से मांगे गए दस्तावेज़/Document required from seller	Bidder Turnover,Certificate (Requested in ATC),OEM Authorization Certificate *In case any bidder is seeking exemption from Experience / Turnover Criteria, the supporting documents to prove his eligibility for exemption must be uploaded for evaluation by the buyer
क्या आप निविदाकारों द्वारा अपलोड किए गए दस्तावेजों को निविदा में भाग लेने वाले सभी निविदाकारों को दिखाना चाहते हैं? संदर्भ मेन् है/Do you want to show documents uploaded by bidders to all bidders participated in bid?	Yes (Documents submitted as part of a clarification or representation during the tender/bid process will also be displayed to other participated bidders after log in)
बिड लगाने की समय सीमा स्वतः नहीं बढ़ाने के लिए आवश्यक बिड की संख्या। / Minimum number of bids required to disable automatic bid extension	2
दिनों की संख्या, जिनके लिए बिड लगाने की समय-सीमा बढ़ाई जाएगी। / Number of days for which Bid would be auto-extended	3
ऑटो एक्सटेंशन अधिकतम कितनी बार किया जाना है। / Number of Auto Extension count	2
बिड से रिवर्स नीलामी सक्रिय किया/Bid to RA enabled	No
बिड का प्रकार/Type of Bid	Single Packet Bid
तकनीकी मूल्यांकन के दौरान तकनीकी स्पष्टीकरण हेतु अनुमत समय /Time allowed for Technical Clarifications during technical evaluation	12 Days
निरीक्षण आवश्यक (सूचीबद्ध निरीक्षण प्राधिकरण /जेम के साथ पूर्व पंजीकृत एजेंसियों द्वारा)/Inspection Required (By Empanelled Inspection Authority / Agencies pre-registered with GeM)	No
मूल्यांकन पद्धति/Evaluation Method	Total value wise evaluation
मध्यस्थता खंड/Arbitration Clause	No
सुलह खंड/Mediation Clause	No

ईएमडी विवरण/EMD Detail

आवश्यकता/Required	No
-------------------	----

ईपीबीजी विवरण /ePBG Detail

आवश्यकता/Required	No
-------------------	----

बोली विभाजन लागू नहीं किया गया/ Bid splitting not applied.

एमआईआई खरीद वरीयता/MII Purchase Preference

एमआईआई खरीद वरीयता/MII Purchase Preference	No
--	----

एमएसई खरीद वरीयता/MSE Purchase Preference

एमएसई खरीद वरीयता/MSE Purchase Preference	Yes
सूक्ष्म और लघु उद्यम मूल उपकरण निर्माताओं को खरीद में प्राथमिकता, यदि उनका मूल्य L1+X% तक की सीमा में हो / Purchase Preference to MSE OEMs available upto price within L1+X%	15
सूक्ष्म और लघु उद्यम को खरीद में प्राथमिकता के लिए बिड की मात्रा का अधिकतम प्रतिशत / Maximum Percentage of Bid quantity for MSE purchase preference	25

1. If the bidder is a Micro or Small Enterprise as per latest orders issued by Ministry of MSME, the bidder shall be relaxed from the eligibility criteria of "Experience Criteria" as defined above subject to meeting of quality and technical specifications. The bidder seeking Relaxation from Experience Criteria, shall upload the supporting documents to prove his eligibility for Relaxation.
2. If the bidder is a Micro or Small Enterprise (MSE) as per latest orders issued by Ministry of MSME, the bidder shall be relaxed from the eligibility criteria of "Bidder Turnover" as defined above subject to meeting of quality and technical specifications. If the bidder itself is MSE OEM of the offered products, it would be relaxed from the "OEM Average Turnover" criteria also subject to meeting of quality and technical specifications. The bidder seeking Relaxation from Turnover, shall upload the supporting documents to prove his eligibility for Relaxation.
3. If the bidder is a DPIIT registered Startup, the bidder shall be relaxed from the the eligibility criteria of "Experience Criteria" as defined above subject to their meeting of quality and technical specifications. The bidder seeking Relaxation from Experience Criteria, shall upload the supporting documents to prove his eligibility for Relaxation.
4. If the bidder is a DPIIT registered Startup, the bidder shall be relaxed from the the eligibility criteria of "Bidder Turnover" as defined above subject to their meeting of quality and technical specifications. If the bidder is DPIIT Registered OEM of the offered products, it would be relaxed from the "OEM Average Turnover" criteria also subject to meeting of quality and technical specifications. The bidder seeking Relaxation from Turnover shall upload the supporting documents to prove his eligibility for Relaxation.
5. Purchase preference will be given to MSEs having valid Udyam Registration and whose credentials are validated online through Udyam Registration portal as defined in Public Procurement Policy for Micro and Small Enterprises (MSEs) Order, 2012 dated 23.03.2012 issued by Ministry of Micro, Small and Medium Enterprises and its subsequent Orders/Notifications issued by concerned Ministry. If the bidder wants to avail themselves of the Purchase preference, the bidder must be the manufacturer / OEM of the offered product on GeM. Traders are excluded from the purview of Public Procurement Policy for Micro and Small Enterprises and hence resellers offering products manufactured by some other OEM are not eligible for any purchase preference. In respect of bid for Services, the bidder must be the Service provider of the offered Service. Relevant documentary evidence in this regard shall be uploaded along with the bid in respect of the offered product or service and Buyer will decide eligibility for purchase preference based on documentary evidence submitted, while evaluating the bid. If L-1 is not an MSE and MSE Seller (s) has / have quoted price within L-1+ 15% (Selected by Buyer) of margin of purchase preference /price band defined in relevant policy, such MSE Seller shall be given opportunity to match L-1 price and contract will be awarded for 25% (selected by Buyer) percentage of total quantity. The buyers are advised to refer the OM No. F.1/4/2021-PPD dated 18.05.2023 [OM No.1 4 2021 PPD dated 18.05.2023](#) for compliance of Concurrent application of Public Procurement Policy for Micro and Small Enterprises Order, 2012 and Public Procurement (Preference to Make in India) Order, 2017. Benefits of MSE will be allowed only if seller is validated on-line in GeM profile as well as validated and approved by Buyer after evaluation of documents submitted.

Pre Bid Detail(s)

मूल्य भिन्नता खंड दस्तावेज़/Pre-Bid Date and Time	प्री-बिड स्थान/Pre-Bid Venue
11-02-2026 15:00:00	DG HQ NDRF Jai Singh Road New Delhi

Eol Light Weight Emergency Tent (LWET) (1 the number pi)

तकनीकी विशिष्टियाँ /Technical Specifications

क्रेता विशिष्टि दस्तावेज़ /Buyer Specification Document	Download
---	--------------------------

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Harvinder Singh	110001,HQ DG, NDRF, 6TH FLOOR, NDCC-II BUILDING, JAI SINGH ROAD, NEW DELHI	1	15

क्रेता द्वारा जोड़ी गई बिड की विशेष शर्तें/Buyer Added Bid Specific Terms and Conditions

1. Generic

OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 25 percent of bid quantity at the time of placement of contract. The purchaser also reserves the right to increase the ordered quantity up to 25% of the contracted quantity during the currency of the contract at the contracted rates. The delivery period of quantity shall commence from the last date of original delivery order and in cases where option clause is exercised during the extended delivery period the additional time shall commence from the last date of extended delivery period. The additional delivery time shall be $(\text{Increased quantity} \div \text{Original quantity}) \times \text{Original delivery period (in days)}$, subject to minimum of 30 days. If the original delivery period is less than 30 days, the additional time equals the original delivery period. The Purchaser may extend this calculated delivery duration up to the original delivery period while exercising the option clause. Bidders must comply with these terms.

2. Turnover

OEM Turn Over Criteria: The minimum average annual financial turnover of the OEM of the offered product during the last three years, ending on 31st March of the previous financial year, should be as indicated in the bid document. Documentary evidence in the form of certified Audited Balance Sheets of relevant periods or a certificate from the Chartered Accountant / Cost Accountant indicating the turnover details for the relevant period shall be uploaded with the bid. In case the date of constitution / incorporation of the OEM is less than 3 year old, the average turnover in respect of the completed financial years after the date of constitution shall be taken into account for this criteria. In case of bunch bids, the OEM of CATEGORY RELATED TO primary product having highest bid value should meet this criterion.

3. OEM

IMPORTED PRODUCTS: In case of imported products, OEM or Authorized Seller of OEM should have a registered office in India to provide after sales service support in India. The certificate to this effect should

be submitted.

अस्वीकरण/Disclaimer

The additional terms and conditions have been incorporated by the Buyer after approval of the Competent Authority in Buyer Organization, whereby Buyer organization is solely responsible for the impact of these clauses on the bidding process, its outcome, and consequences thereof including any eccentricity / restriction arising in the bidding process due to these ATCs and due to modification of technical specifications and / or terms and conditions governing the bid. If any clause(s) is / are incorporated by the Buyer regarding following, the bid and resultant contracts shall be treated as null and void and such bids may be cancelled by GeM at any stage of bidding process without any notice:-

1. Definition of Class I and Class II suppliers in the bid not in line with the extant Order / Office Memorandum issued by DPIIT in this regard.
2. Seeking EMD submission from bidder(s), including via Additional Terms & Conditions, in contravention to exemption provided to such sellers under GeM GTC.
3. Publishing Custom / BOQ bids for items for which regular GeM categories are available without any Category item bunched with it.
4. Creating BoQ bid for single item.
5. Mentioning specific Brand or Make or Model or Manufacturer or Dealer name.
6. Mandating submission of documents in physical form as a pre-requisite to qualify bidders.
7. Floating / creation of work contracts as Custom Bids in Services.
8. Seeking sample with bid or approval of samples during bid evaluation process. (However, in bids for [attached categories](#), trials are allowed as per approved procurement policy of the buyer nodal Ministries)
9. Mandating foreign / international certifications even in case of existence of Indian Standards without specifying equivalent Indian Certification / standards.
10. Seeking experience from specific organization / department / institute only or from foreign / export experience.
11. Creating bid for items from irrelevant categories.
12. Incorporating any clause against the MSME policy and Preference to Make in India Policy.
13. Reference of conditions published on any external site or reference to external documents/clauses.
14. Asking for any Tender fee / Bid Participation fee / Auction fee in case of Bids / Forward Auction, as the case may be.
15. Buyer added ATC Clauses which are in contravention of clauses defined by buyer in system generated bid template as indicated above in the Bid Details section, EMD Detail, ePBG Detail and MII and MSE Purchase Preference sections of the bid, unless otherwise allowed by GeM GTC.
16. In a category based bid, adding additional items, through buyer added additional scope of work/ additional terms and conditions/or any other document. If buyer needs more items along with the main item, the same must be added through bunching category based items or by bunching custom catalogs or bunching a BoQ with the main category based item, the same must not be done through ATC or Scope of Work.

Further, if any seller has any objection/grievance against these additional clauses or otherwise on any aspect of this bid, they can raise their representation against the same by using the Representation window provided in the bid details field in Seller dashboard after logging in as a seller within 4 days of bid publication on GeM. Buyer is duty bound to reply to all such representations and would not be allowed to open bids if he fails to reply to such representations.

All GeM Sellers/Service Providers shall ensure full compliance with all applicable labour laws, including the provisions, rules, schemes and guidelines under the four Labour Codes i.e. the Code on Wages, 2019; the Industrial Relations Code, 2020; the Occupational Safety, Health and Working Conditions Code, 2020; and the Code on Social Security, 2020 as and when notified and brought into force by the Government of India.

For all provisions of the Labour Codes that are pending operationalisation through rules, schemes or notifications, the corresponding provisions of the pre-existing labour enactments (such as The Minimum Wages Act, 1948, The Payment of Wages Act, 1936, The Payment of Bonus Act, 1965, The

Equal Remuneration Act, 1976, The Payment of Gratuity Act, 1972, etc. and relevant State Rules) shall continue to remain applicable.

The Seller/ Service Providers shall, therefore, be responsible for ensuring compliance under:

- **All notified and enforceable provisions of the new Labour Codes as mentioned hereinabove; and**
- **All operative provisions of the erstwhile Labour Laws until their complete substitution.**

All obligations relating to wages, social security, safety, working conditions, industrial relations etc. and any other statutory requirements shall be strictly met by the Seller/ Service Provider. Any non-compliance shall constitute a breach of the contract and shall entitle the Buyer to take appropriate action in accordance with the contract and applicable law.

[यह बिड सामान्य शर्तों के अंतर्गत भी शासित है /This Bid is also governed by the General Terms and Conditions](#)

जेम की सामान्य शर्तों के खंड 26 के संदर्भ में भारत के साथ भूमि सीमा साझा करने वाले देश के बिडर से खरीद पर प्रतिबंध के संबंध में भारत के साथ भूमि सीमा साझा करने वाले देश का कोई भी बिडर इस निविदा में बिड देने के लिए तभी पात्र होगा जब वह बिड देने वाला सक्षम प्राधिकारी के पास पंजीकृत हो। बिड में भाग लेते समय बिडर को इसका अनुपालन करना होगा और कोई भी गलत घोषणा किए जाने

व इसका अनुपालन न करने पर अनुबंध को तत्काल समाप्त करने और कानून के अनुसार आगे की कानूनी कार्रवाई का आधार होगा।/In terms of GeM GTC clause 26 regarding Restrictions on procurement from a bidder of a country which shares a land border with India, any bidder from a country which shares a land border with India will be eligible to bid in this tender only if the bidder is registered with the Competent Authority. While participating in bid, Bidder has to undertake compliance of this and any false declaration and non-compliance of this would be a ground for immediate termination of the contract and further legal action in accordance with the laws.

---धन्यवाद/Thank You---